

STU1 Lite

SYSTEMS & TECHNOLOGY CORP.
GPS Vehicle Tracker



Features

- Cost effective and easy installation
- SMS, GPRS TCP/UDP, FTP communications
- 50 geofence reports (Circular/Polygonal Zones)
- Remote configuration
- Real-time tracking (Time, Distance Interval or Intelligent Mode, and Heading)
- Intelligent power management
- Power low/lost alarm
- Journey report wireless download
- GSM/ GPRS simultaneously
- Mileage report
- 50 user-defined reports
- Firmware upgrade over the air (via GPRS from FTP)
- Up to 120,000 data logs



www.suprtrack.com



Specification

- Dimensions (L x W x H): 72mm x 108mm x 31mm
 - Weight: 165g
 - GPS Receiver: 50 Channels or Above
 - Datum: WGS-84
 - Power Source: 8-30V DC
 - Power Consumption: 72mA@12VDC (Operation Mode)
8mA@12VDC (Standby Mode)
6mA@12VDC (Deep Sleep Mode)
 - Operating Temperature: -20°C ~ +70°C
 - Communications: GSM 850/ 900/ 1800/ 1900, SMS, GPRS TCP/UDP, FTP
 - Serial Ports: 1 RS-232 Port (Configurable) ⊙
 - Input Ports: 3 Digital Inputs (2 Positive Triggers & 1 Negative Triggers) ; 1 Analog Input (12-bit Resolution)
 - Output Ports: 2 Outputs (Negative Triggers, Max. Sink Current 300mA)
 - Backup Battery: Li-Ion, 1050mAh ⊙
- ⊙ STU1 Lite only

Accessories

Standard

- Power Cable
- GPS Antenna

Option

- I/O Cable
- CAN Bus Kit (CAN Bridge) ⊙
- Li-Ion Backup Battery ⊙
- Mobile Data Terminal ⊙
- RFID Reader ⊙
- Support CAN-bus Solution ⊙
- RS-232 Cable ⊙

⊙ STU1 Lite only

Applications

- Vehicle Real-time Tracking
- Vehicle Data Warehouse
- Vehicle Security/ Rescue/ Anti-Hijack
- Mobile Asset Tracking
- Fleet Management
- Location Based Service

The specification may be subject to change without prior notice.

PTCRB **CE** **FC**

